

# commBOX Interactive Classic Specs

## Models



Classic 60  
CB3060L-4NG4K



Classic 70  
CB3070L-4NG4K



Classic 80  
CB3080L-4NG4K



Classic 90  
CB3090L-4NG4K



Classic 103  
CB30103L-4NG4K

## SKU

## Screen

Resolution	UD 3840x2160 @60Hz	UD 3840x2160 @60Hz	UD 3840x2160 @60Hz	UD 3840x2160 @60Hz	UD 3840x2160 @60Hz
Brightness	450cd / m2	450cd / m2	450cd / m2	350cd / m2	500cd / m2
Viewing Angle	178'	178'	178'	178'	178'
Noise	Below 40dB 25C	Below 40dB 25C	Below 40dB 25C	Below 40dB 25C	Below 40dB 25C
Surface Temp	Below 10 at 24C	Below 10 at 24C	Below 10 at 24C	Below 10 at 24C	Below 10 at 24C
Operating Con	5C to 35C	5C to 35C	5C to 35C	5C to 35C	5C to 35C
Power Req	AC 100 to 240V, 50/60Hz Power Supply			AC 100 to 240V, 50/60Hz Power Supply	
Power Max	130W	260W	470W	470W	520W
Power Average	110W	240W	430W	430W	480W
Touch Points	4 (10 optional) Fingertips or any tips			4 (10 optional) Fingertips or any tips	
Touch Technology	Infra-Red & Optical			Infra-Red & Optical	
LED Display	LG Commercial Grade	LG Commercial Grade	SAMSUNG Commercial Grade	LG Commercial Grade	LG Commercial Grade

## Dimensions

Touch Area	60"	70"	80"	90"	103"
Display Area	55"	65"	75"	86"	98"
Screen	1413(W) x 838(H) x 95(D)mm	1632(W) x 959(H) x 106(D)mm	1840(W) x 1085(H) x 126(D)mm	2065(W) x 1222(H) x 125(D)mm	2345(W) x 1369(H) x 125(D)mm
Packed	1590(W) x 960(H) x 270(D)mm	1850(W) x 1100(H) x 320(D)mm	2050(W) x 1225(H) x 350(D)mm	2275(W) x 1360(H) x 400(D)mm	2600(W) x 1550(H) x 560(D)mm

## Weight

Screen	50kg	68kg	98kg	122kg	134kg
Packed	57kg	81kg	116kg	147kg	154kg

## Accessories

HDMI Cable, USB Cable, Stylus Pen, Cleaning Cloth

HDMI Cable, USB Cable, Stylus Pen, Cleaning Cloth

## Speakers

15W x 2 Internal Speakers 15W x 2 Speaker Out 

15W x 2 Internal Speakers 15W x 2 Speaker Out 

## Input/Output

Input: VGA + 3.5 Stereo Audio, Component, 4 X HDMI, USB A for content, USB B for Touch, RS232  
Output: Speaker 2 x 3.5 Mono, SPDIF, Line level output

Input: VGA + 3.5 Stereo Audio, Component, 4 X HDMI, USB A for content, USB B for Touch, RS232  
Output: Speaker 2 x 3.5 Mono, SPDIF, Line level output