

# commBOX Interactive Table Specs

## Models



Table 32S



Table 42S



Table 32T



Table 46T

## SKU

CBTAB32S

CBTAB42S


CBTAB32T

CBTAB42T

## Screen


Resolution	1920 x 1080 @60Hz	1920 x 1080 @60Hz	1920 x 1080 @60Hz	1920 x 1080 @60Hz
Brightness	350 cd/m2	400 cd/m2	350 cd/m2	500CD/m2
Viewing Angle	178'	178'	178'	178'
Noise	Below 40dB 25C	Below 40dB 25C	Below 40dB 25C	Below 40dB 25C
Surface Temp	Below 10 at 24C	Below 10 at 24C	Below 10 at 24C	Below 10 at 24C
Operating Con	5C to 35C	5C to 35C	5C to 35C	5C to 35C
Contrast Ratio	3000 : 1	1000 : 1	3000 : 1	4000 : 1
Touch Points	10 (32 optional) Fingertips			
Touch Technology	Projected Capacitive			
LED Display	SAMSUNG Commercial Grade			

## Dimensions




Product 1084(W) x 454(H) x 678(D) mm

Packed 1175(W) x 970(H) x 230(D) mm




Product 1272(W) x 454(H) x 772(D) mm

Packed 1355(W) x 1060(H) x 295(D) mm



Product 1282(W) x 954(H) x 676(D) mm

Packed 1365(W) x 960(H) x 315(D) mm



Product 1597(W) x 954(H) x 851(D) mm

Packed 1677(W) x 1135(H) x 325(D) mm

## Weight

Product	30kg	37kg	39kg	67kg
Packed	31kg	39kg	40kg	69kg

## Power

AC 100 to 240V, 50/60Hz Power Supply

## Accessories

HDMI cable

USB cable

Remote Control

## Sync Frequency

Analogue H31.47~67.5kHz, V47~63Hz, Digital H15.62~67.50kHz, V24~60Hz

## Speakers

7Wx2 (stereo speaker) Internal Speakers

## Input/Output

VGA, DVI-D, HDMI, 3.5 stereo, RS-232C, USB