

commBOX Interactive Pulse Specs

Models



Pulse 49

CBINTP494K



Pulse 55

CBINTP554K



Pulse 65

CBINTP654K



Pulse 75


CBINTP754K

SKU

Screen

Resolution	UD 3840x2160 @60Hz	UD 3840x2160 @60Hz	UD 3840x2160 @60Hz	UD 3840x2160 @60Hz
Brightness	500cd/m2	500cd/m2	500cd / m2	410cd / m2
Viewing Angle	178'	178'	178'	178'
Noise	Below 40dB 25C	Below 40dB 25C	Below 40dB 25C	Below 40dB 25C
Surface Temp	Below 10 at 24C	Below 10 at 24C	Below 10 at 24C	Below 10 at 24C
Operating Con	5C to 35C	5C to 35C	5C to 35C	5C to 35C
Power Req	AC 100 to 240V, 50/60Hz Power Supply		AC 100 to 240V, 50/60Hz Power Supply	
Power Max	112W	130W	170W	270W
Power Average	98W	110W	140W	240W
Touch Points	20 (50 optional) Fingertips or Passive/Active Pens		20 (50 optional) Fingertips or Passive/Active Pens	
Touch Technology	Projected Capacitive		Projected Capacitive	
LED Display	LG Commercial Grade	LG Commercial Grade	LG Commercial Grade	LG Commercial Grade

Dimensions



49"

Touch Area

Display Area

Screen

1156(W) x 686(H)
x 116(D)mm

Packed


1325(W) x 940(H)
x 280(D)mm



55"

1282(W) x 752(H)
x 127(D)mm

1530(W) x 1030(H)
x 250(D)mm



65"

1512(W) x 887(H)
x 105(D)mm

1690(W) x 1020(H)
x 290(D)mm



75"

1707(W) x 985(H)
x 116(D)mm

1881(W) x 1180(H)
x 315(D)mm

Weight

Screen

44kg

58kg

62kg

74kg

Packed

56kg

60kg

76kg

86kg

Accessories

HDMI Cable, USB Cable, Stylus Pen, Cleaning Cloth

HDMI Cable, USB Cable, Stylus Pen, Cleaning Cloth

Speakers

10W x 2 Internal Speakers
10W x 2 Speaker Out

15W x 2 Internal Speakers
15W x 2 Speaker Out

15W x 2 Internal Speakers 15W x 2 Speaker Out



Input/Output

Input: VGA + 3.5 Stereo Audio, Component, 4 X HDMI,
USB A for content, USB B for Touch, RS232
Output: Speaker 2 x 3.5 Mono, SPDIF, Line level output

Input: VGA + 3.5 Stereo Audio, Component, 4 X HDMI,
USB A for content, USB B for Touch, RS232
Output: Speaker 2 x 3.5 Mono, SPDIF, Line level output