

commBOX Interactive Classic Specs

Models					
SKU	Classic 60 CB3060L-4NG4K	Classic 70 CB3070L-4NG4K	Classic 80 CB3080L-4NG4K	Classic 90 CB3090L-4NG4K	Classic 103 CB30103L-4NG4K
Screen					
Resolution	UD 3840x2160 @60Hz	UD 3840x2160 @60Hz	UD 3840x2160 @60Hz	UD 3840x2160 @60Hz	UD 3840x2160 @60Hz
Brightness	450cd / m2	450cd / m2	450cd / m2	350cd / m2	500cd / m2
Viewing Angle	178°	178°	178°	178°	178°
Noise	Below 40dB 25C	Below 40dB 25C	Below 40dB 25C	Below 40dB 25C	Below 40dB 25C
Surface Temp	Below 10 at 24C	Below 10 at 24C	Below 10 at 24C	Below 10 at 24C	Below 10 at 24C
Operating Con	5C to 35C	5C to 35C	5C to 35C	5C to 35C	5C to 35C
Power Req	AC 100 to 240V, 50/60Hz Power Supply		AC 100 to 240V, 50/60Hz Power Supply		
Power Max	130W	260W	470W	470W	520W
Power Average	110W	240W	430W	430W	480W
Touch Points	4 / 10 Fingertips or any tips		4 /10 Fingertips or any tips		
Touch Technology	Optical		Optical		
LED Display	LG Commercial Grade	LG Commercial Grade	LG Commercial Grade	LG Commercial Grade	LG Commercial Grade
Dimensions					
Touch Area	60"	70"	80"	90"	103"
Display Area	55"	65"	75"	86"	98"
Screen	1413(W) x 838(H) x 102(D)mm	1638(W) x 960(H) x 108(D)mm	1840(W) x 1085(H) x 128(D)mm	2093(W) x 1234(H) x 125(D)mm	2368(W) x 1393(H) x 141(D)mm
Packed	1590(W) x 960(H) x 270(D)mm	1850(W) x 1100(H) x 320(D)mm	2050(W) x 1225(H) x 350(D)mm	2275(W) x 1360(H) x 400(D)mm	2600(W) x 1550(H) x 560(D)mm
Weight					
Screen	50kg	68kg	98kg	122kg	134kg
Packed	57kg	81kg	116kg	147kg	154kg
Accessories	HDMI Cable, USB Cable, Stylus Pen, Cleaning Cloth			HDMI Cable, USB Cable, Stylus Pen, Cleaning Cloth	
Speakers	15W x 2 Internal Speakers 15W x 2 Speaker Out 			15W x 2 Internal Speakers 15W x 2 Speaker Out 	
Input/Output	Input: VGA + 3.5 Stereo Audio, Component, 4 X HDMI, USB A for content, USB B for Touch, RS232 Output: Speaker 2 x 3.5 Mono, SPDIF, Line level output			Input: VGA + 3.5 Stereo Audio, Component, 4 X HDMI, USB A for content, USB B for Touch, RS232 Output: Speaker 2 x 3.5 Mono, SPDIF, Line level output	