

commBOX Interactive Pulse Specs

Models



Pulse 49

CBINTP494K



Pulse 55

CBINTP554K



Pulse 65

CBINTP654K



Pulse 75

CBINTP754K

SKU

Screen

| | | | | |
|------------------|----------------------------------------------------|------------------------|----------------------------------------------------|------------------------|
| Resolution | UD 3840x2160 @60Hz | UD 3840x2160 @60Hz | UD 3840x2160 @60Hz | UD 3840x2160 @60Hz |
| Brightness | 500cd/m2 | 500cd/m2 | 500cd / m2 | 410cd / m2 |
| Viewing Angle | 178' | 178' | 178' | 178' |
| Noise | Below 40dB 25C | Below 40dB 25C | Below 40dB 25C | Below 40dB 25C |
| Surface Temp | Below 10 at 24C | Below 10 at 24C | Below 10 at 24C | Below 10 at 24C |
| Operating Con | 5C to 35C | 5C to 35C | 5C to 35C | 5C to 35C |
| Power Req | AC 100 to 240V, 50/60Hz Power Supply | | AC 100 to 240V, 50/60Hz Power Supply | |
| Power Max | 112W | 130W | 170W | 270W |
| Power Average | 98W | 110W | 140W | 240W |
| Touch Points | 20 (50 optional) Fingertips or Passive/Active Pens | | 20 (50 optional) Fingertips or Passive/Active Pens | |
| Touch Technology | Projected Capacitive | | Projected Capacitive | |
| LED Display | LG Commercial Grade | LG Commercial Grade | LG Commercial Grade | LG Commercial Grade |

Dimensions



49"

49"

1156(W) x 686(H)
x 116(D)mm

1325(W) x 940(H)
x 280(D)mm




55"

55"

1282(W) x 752(H)
x 114(D)mm

1550(W) x 1050(H)
x 260(D)mm



65"

65"

1512(W) x 887(H)
x 116(D)mm

1686(W) x 1020(H)
x 280(D)mm



75"

75"

1707(W) x 985(H)
x 116(D)mm

1881(W) x 1180(H)
x 315(D)mm

Weight

| | | | | |
|--------|------|------|------|------|
| Screen | 44kg | 50kg | 62kg | 74kg |
| Packed | 56kg | 58kg | 75kg | 86kg |

Accessories

HDMI Cable, USB Cable, Stylus Pen, Cleaning Cloth

HDMI Cable, USB Cable, Stylus Pen, Cleaning Cloth

Speakers

10W x 2 Internal Speakers
10W x 2 Speaker Out

15W x 2 Internal Speakers
15W x 2 Speaker Out

15W x 2 Internal Speakers 15W x 2 Speaker Out



Input/Output

Input: VGA + 3.5 Stereo Audio, Component, 4 X HDMI,
USB A for content, USB B for Touch, RS232
Output: Speaker 2 x 3.5 Mono, SPDIF, Line level output

Input: VGA + 3.5 Stereo Audio, Component, 4 X HDMI,
USB A for content, USB B for Touch, RS232
Output: Speaker 2 x 3.5 Mono, SPDIF, Line level output